


ESD5431Z
1-Line, Bi-directional, Transient Voltage Suppressor
<http://www.sh-willsemi.com>
Descriptions


The ESD5431Z is a bi-directional TVS (Transient Voltage Suppressor). It is specifically designed to protect sensitive electronic components which are connected to low speed data lines and control lines from over-stress caused by ESD (Electrostatic Discharge), EFT (Electrical Fast Transients) and Lightning.

The ESD5431Z may be used to provide ESD protection up to $\pm 30\text{kV}$ (contact discharge) according to IEC61000-4-2, and withstand peak pulse current up to 10A (8/20 μs) according to IEC61000-4-5.

The ESD5431Z is available in DFN0603-2L package. Standard products are Pb-free and Halogen-free.


DFN0603-2L (Bottom View)

Circuit diagram
Features

- Stand-off voltage: $\pm 3.3\text{V}$ Max
- Transient protection for each line according to IEC61000-4-2 (ESD): $\pm 30\text{kV}$ (contact discharge)
IEC61000-4-4 (EFT): 40A (5/50ns)
IEC61000-4-5 (surge): 10A (8/20 μs)
- Capacitance: $C_J = 17.5\text{pF}$ typ.
- Low leakage current: $I_R = 1\text{nA}$ typ.
- Low clamping voltage: $V_{CL} = 8\text{V}$ typ. @ $I_{PP} = 16\text{A}$ (TLP)
- Small package



Y = Device code

* = Month code

Marking (Top View)
Applications


- Cellular handsets
- Computers and peripherals
- Microprocessors
- Portable Electronics
- Notebooks

Order information

Device	Package	Shipping
ESD5431Z-2/TR	DFN0603-2L	10000/Tape&Reel

Absolute maximum ratings

Parameter	Symbol	Rating	Unit
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	100	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{PP}	10	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	kV
ESD according to IEC61000-4-2 contact discharge		± 30	
Junction temperature	T_J	125	$^{\circ}C$
Operating temperature	T_{OP}	-40~85	$^{\circ}C$
Lead temperature	T_L	260	$^{\circ}C$
Storage temperature	T_{STG}	-55~150	$^{\circ}C$







Electrical characteristics ($T_A=25^{\circ}C$, unless otherwise noted)

Definitions of electrical characteristics


Electrical characteristics (T_A=25 °C, unless otherwise noted)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Reverse stand-off voltage	V _{RWM}				±3.3	V
Reverse leakage current	I _R	V _{RWM} = 3.3V		<1	100	nA
Reverse breakdown voltage	V _{BR}	I _{BR} = 1mA	3.4			V
Reverse holding voltage	V _{HOLD}	I _{HOLD} = 50mA	3.4			V
Clamping voltage ¹⁾	V _{CL}	I _{PP} = 16A, t _p = 100ns		8		V
Clamping voltage ²⁾	V _{CL}	V _{ESD} = 8kV		8		V
Clamping voltage ³⁾	V _{CL}	I _{PP} = 1A, t _p = 8/20μs			6	V
		I _{PP} = 5A, t _p = 8/20μs			8	V
		I _{PP} = 10A, t _p = 8/20μs			10	V
Dynamic resistance ¹⁾	R _{DYN}			0.20		Ω
Junction capacitance	C _J	V _R = 0V, f = 1MHz		17.5	22	pF
		V _R = 3.3V, f = 1MHz		12.5	16	pF


Notes:

- 1) TLP parameter: Z₀ = 50Ω, t_p = 100ns, t_r = 2ns, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
- 2) Contact discharge mode, according to IEC61000-4-2.
- 3) Non-repetitive current pulse, according to IEC61000-4-5.


Typical characteristics ($T_A=25^\circ\text{C}$, unless otherwise noted)

8/20 μs waveform per IEC61000-4-5

Contact discharge current waveform per IEC61000-4-2

Clamping voltage vs. Peak pulse current

Capacitance vs. Reverse voltage

Non-repetitive peak pulse power vs. Pulse time

Power derating vs. Ambient temperature

Typical characteristics ($T_A=25^\circ\text{C}$, unless otherwise noted)






ESD clamping
 (+8kV contact discharge per IEC61000-4-2)



ESD clamping
 (-8kV contact discharge per IEC61000-4-2)



TLP Measurement

Package outline dimensions
DFN0603-2L

Top View

Bottom View

Side View
Recommend land pattern (Unit: mm)


Symbol	Dimensions in Millimeters		
	Min.	Typ.	Max.
A	0.230	-	0.340
A1	0.000	-	0.050
A3	0.102 REF.		
D	0.550	0.600	0.670
E	0.250	0.300	0.370
b	0.215	-	0.295
e	0.400 BSC		
L	0.115	-	0.195

Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met.